

## ENDURABLE SURFACE CLEANER

Endurable Surface Cleaner is a concentrated cleaner capable of tackling the toughest contaminants, including oils, greases, stains, and more.

### ADVANTAGES

- Easy to use - simply add water
- Low odor allows for uses inside and outside
- Leaves no residue - perfect for application on substrates requiring no bond breakers
- High concentration allows for adjustable strengths to accommodate multiple applications

### WHERE TO USE

Product may be used on any surface. This product is especially well suited for concrete. At low dilution ratios, the product is excellent against oils, and at high dilution ratios is excellent for general purpose cleaning.

### PACKAGING

Concentrate that makes up to 8.5 gallons and concentrate that makes up to 85 gallons.

### TEST AREA

Performing a test area is advisable to make sure the product is suitable for your surface.

### COVERAGE RATES

100 - 350 square feet per gallon depending on porosity of surface and level of preparation

### PRODUCT AVAILABILITY

Product is available at retail distributors around the world. Visit the Endurable website to find the nearest distributor.

### DILUTION RATIOS

- 16 to 1 for basic cleaning (makes 8.5 gallons or 85 for larger size)
- 9 to 1 for medium stains - non-oil-based stains or contaminants (makes 5 gallons 50 gallons for larger size)
- 3 to 1 for heavy stains - oil-based stains and contaminants (makes 2 gallons or 20 gallons for larger size)

May also be used undiluted for the most difficult contaminants.

### APPLICATION TOOL OPTIONS

- Pump up sprayer with a .05 to .15 gpm conical tip at 40 psi (on smooth surface concrete use a maximum .05 - .08 gpm conical tip)
- Mop
- Broom

### APPLICATION INSTRUCTIONS

Apply with a mop, sprayer, or broom. Allow the product to work for a few minutes before agitation with mop or brush. If necessary, repeat the process. Using a pressure washer will yield best results whenever the situation allows. If pressure washer is not an option, clean area with a damp mop after application to remove any residual dirt or contaminants brought to the surface by the cleaner.

**DO NOT ALLOW PRODUCT TO DRY BEFORE AGITATION OR PROCESS WILL NEED TO BE REPEATED TO LOOSEN CONTAMINANTS FROM SURFACE.**

## **STORAGE AND SHELF LIFE**

When stored in original unopened containers at temperatures 35 - 95 degrees Fahrenheit, best performance is achieved within 3 years from the date of manufacture.

## **SAFETY**

Use with proper ventilation. May cause eye and skin irritation. If you experience headaches, dizziness, or watery eyes, you may wear an Organic Vapor Respirator during application. As with any chemical, respirators, eye protection, and gloves are recommended.

## **WARRANTY**

Evaluate whether this product is suitable for your intended application. Conditions of product use are outside of our control and vary widely, the following is made in lieu of all express or implied warranties of merchantability: Our only obligation and your only remedy are replacement of product, at the option of HDIP INC. In no case will HDIP INC be liable for any direct, indirect, special, incidental, or consequential damages including lost profits, goodwill, or business opportunity.

## **TECHNICAL ASSISTANCE**

For technical questions or support, call 800-910-3120 ext. 1 between the hours of 8:30 am to 4:30 pm PST.