

F1 SEALER™

FAST-DRYING, DURABLE, AND BURNISHABLE SEALER

THIS SINGLE COMPONENT SEALER IS AN EXCELLENT REPLACEMENT FOR SOLVENT-BASED ACRYLIC SEALERS. APPLICATION DURING RECOAT WINDOW OVER ENDURABLE CONCRETE SEALER RESULTS IN A RICH LOOK USUALLY ACHIEVED WITH FLOOR WAX, YET YIELDING MUCH LONGER-TERM RESULTS.

- GLOSS & MATTE FINISH
- GOOD DURABILITY
- LOW VOC CONTENT AND LOW ODOR
- QUICK TO DRY
- EASY TO APPLY
- SPRAY, ROLL, OR MICRO-FIBER APPLICATION
- GOOD UV STABILITY
- GOOD ELASTICITY
- GOOD CHEMICAL RESISTANCE



CONCRETE ARMOR™

CUTTING EDGE EPOXY TECHNOLOGY

- LOW VOC CONTENT
- UNBELIEVABLE BOND STRENGTH OVER 1000 PSI (4 TO 5 TIMES STRONGER THAN MOST COATINGS)
- IMPRESSIVE DRY TIMES YIELD A GREAT RETURN-TO-SERVICE
- PENDULUM HARDNESS OVER 320 (STANDARD COATINGS ARE USUALLY 30 - 120)
- WORKS GREAT AS PRIMER OR TOPCOAT
- MAY BE USED IN CONJUNCTION WITH ENDURABLE CONCRETE SEALER AND STAINS
- POLYMERIC CHIPS, QUARTZ, OR SAND MAY BE BROADCASTED INTO PRODUCT TO CREATE DECORATIVE SURFACES

CONCRETE HARDENER™

NANO PARTICLE SIZE, FAST REACTION TIME, AND DOES NOT REQUIRE AGITATION

WHEN LOOKING TO CHOOSE THE BEST HARDENER, ONE SHOULD LOOK AT THE SUPERIOR TECHNOLOGY OF SILICA OVER THE OTHER SILICATE FAMILIES. WITH A PARTICLE SIZE BETWEEN 3-8 NANOMETERS AND THE ABILITY TO BOND TO ITSELF, ENDURABLE CONCRETE HARDENER PRODUCES MORE REACTION POINTS AND CAN TRAVEL FARTHER INTO CONCRETE. THIS PROCESS DELIVERS A SUPERIOR FINISHED FLOOR OVER OTHER SILICATED HARDENERS.



POLISH PROTECTOR™

THE TECHNOLOGY PROVIDES MULTIPLE ADVANTAGES OVER STANDARD POLISHED CONCRETE SEALERS

- GLOSS & MATTE FINISH
- QUICK TO DRY
- EASY MICRO-FIBER APPLICATION
- LOW VOC CONTENT AND LOW ODOR
- IMPRESSIVE CHEMICAL RESISTANCE
- GOOD DURABILITY
- GOOD UV STABILITY
- GOOD AGAINST HOT TIRE PICK-UP